

LEYLAND-TRIUMPH SALES COMPANY, INC.

WESTERN ZONE



TO: ALL TRIUMPH DEALERS - WESTERN ZONE

DEPT: SERVICE DEPARTMENT

BULLETIN T-65-32

SUBJECT: TIRE PRESSURES FOR GOODYEAR 165-15 G800
AND DUNLOP 590-15 C41 RAYON TIRES

DATE: JUNE 24, 1965

This is to alert you of the possibility of receiving the above mentioned tires on the TR-4A as original equipment but in limited quantities. This has been done just to supplement the supply of tires.

As you are aware, tire pressures are quite critical and if not maintained at correct pressures will result in peculiar handling characteristics so your attention is drawn to the tire pressures below:

Goodyear 165-15 G800, 24 p.s.i. front, 28 p.s.i. rear on both I.R.S. and rigid axle cars. These pressures are also suitable for sustained speeds up to 110 M.P.H. Goodyear 590-15 G8s same as Grand Prix listed.

Dunlop 590-15 C41 Rayon, 18 p.s.i. front, 22 p.s.i. rear for sustained speeds to 85 M.P.H. 26 p.s.i. front 30 p.s.i. rear for sustained speeds up to 110 M.P.H. These pressures apply to both I.R.S. and rigid axle vehicles.

All other tires which may be found on TR4A models as original equipment should follow specifications listed in the Owner's Handbook on page 58, unless otherwise indicated.