



TO: ALL TRIUMPH DEALERS - WESTERN ZONE

DEPT: SERVICE DEPARTMENT

BULLETIN T-67-17

SUBJECT: TIRE PRESSURE RECOMMENDATIONS

DATE: APRIL 6, 1967


To assist In the answering of queries for correct tire pressure of Triumph vehicles, we are pleased to list the following information regarding the recommended tire Inflation pressures.

<u>MODEL</u>	<u>TIRE SIZE</u>	<u>2 UP</u>		<u>LADEN</u>	
1200 Sedan	5.20-13	21	24	21	28
1200 Convertible	5.20-13	21	24	-	-
Triumph G.T. Six	155-13	20	24	20	24
Spitfire Mark II	5.20-13*	18	24	-	-
Spitfire Mark II	5.20-13 Michelin X	21	27	-	-
Spitfire Mark II	145-13X	18	26	-	-
Spitfire Mark II	145-13 SP.	21	26	-	-
Triumph 2000	6.50-13 Dunlop C41	24	24	24	24
Triumph 2000	6.50-13 Goodyear G800	30	all	round	for
sustained high speed motoring above 85 mph.					
Triumph 2000	175-13 SP	26	26	26	26
Triumph 2000	175-13 Goodyear G800	26	26	26	26
Triumph 2000	5.90-13 Michelin X	27	34	27	34
TR-4A - I.R.S.	6.95-15 Goodyear G.P.	17	21	-	-
TR-4A - Live Axle	6.95-15 Goodyear G.P.	17	23	-	-
TR-4A - Live Axle&IRS	165-15 Dunlop S.P.	24	28	-	-

* For sustained high speeds see Handbook.

LEYLAND-TRIUMPH SALES COMPANY, INC.

WESTERN ZONE



TO: ALL TRIUMPH DEALERS - WESTERN ZONE

DEPT: SERVICE DEPARTMENT

BULLETIN T-67-17

SUBJECT: TIRE PRESSURE RECOMMENDATIONS

DATE: APRIL 6, 1967

<u>MODEL</u>	<u>TIRE SIZE</u>	<u>2 UP</u>		<u>LADEN</u>	
TR-4A - Live Axle&IRS	165-15 Goodyear G800	24	28	-	-
TR-4A - I.R.S.	165-15 Michelin X	17	21	-	-
TR-4A - Live Axle	165-15 Michelin X	17	25	-	-
TR-4A - IRS	5.90-15 Goodyear G8S	17	21	-	-
TR-4A - Live Axle	5.90-15 Goodyear	19	23	-	-
TR-4A - IRS&Live Axle	5.90-15 Dunlop C41	18	22		
for sustained speeds up to 85 mph.					
TR-4A - IRS&Live Axle	5.90-15 Dunlop C41	26	30		
for sustained speeds up to 110 mph.					

For intermediate sustained speeds,
pressures should be increased 1 psi for
each increment of 3 mph.